

## Data Sheet

**Type Number** ..... 20315  
**Designation IEC** ..... SR 716 SW  
**System** ..... Silver oxide / Zinc / NaOH



**Nominal Voltage** ..... 1,55 V  
**Typical Capacity C** ..... 19 mAh  
 Load 30 kOhm, at 20°C down to 1.2 V

**Weight (approx.)** ..... 0,33 g  
**Volume** ..... 0,09 ccm  
**Coding**..... Date of Manufacturing  
 Month / Year

|                           |       |      |
|---------------------------|-------|------|
| <b>Temperature Ranges</b> | min.  | max. |
| Storage .....             | -10°C | 60°C |
| Discharge .....           | -10°C | 60°C |

|                    |      |      |
|--------------------|------|------|
| <b>Dimensions</b>  | min  | max. |
| Diameter (Ø).....  | 7,75 | 7,90 |
| Height (A/B) ..... | 1,47 | 1,65 |

**Segment** ..... Watch

**Main Applications** ..... Watch  
 Photo  
 Electronic

**Typical Capacities (at 20°C)**

| Discharge Type           | Load    | End Voltage: | 1.2 V |
|--------------------------|---------|--------------|-------|
| Continuous<br>24h/d, 7d/ | 30000 Ω | Time:        | 330 h |