NiMH Battery Charger (CHFC2)

North American Region
Download User Manual

Universal Charger

EASY

- Easy-to-read LCD screen shows the charging status of the batteries inside

VERSATILE

- Charges up to 8 AA, 8 AAA, 4C, 4D or 1 9V NiMH rechargeable batteries

FAST & EFFICIENT

- Charges 4 AA NiMH batteries in approximately 3 hours

3

Before Using Your Charger:
Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Best used with Energizer NiMH batteries.

Product Detail:

Designation: Family Charger
Color: Black and Silver
Charging Current: 2 or 4 "AA" 1100mA (1 battery per bay)
1 or 2 "AA-C-D" 1100mA (1 battery per bay)
6 or 8 "AA" 550mA (2 batteries per bay)
3 or 4 "AA-C-D" 550mA (2 batteries per bay)
1 to 4 "AAA" 450mA
2 or 4 "AAA" 450 mA
6 or 8 "AAA" 450 mA
1 "9V" 30mA

AA, C, and D charging current is based on the number of batteries in each bay. One battery per bay will give maximum charging current and shortest charging times. Two batteries per bay reduces charging current therefore increasing charge time.

Trickle Charge: "AA-C-D" 50mA
"AAA" 25mA
"9V" No Trickle Charge
Shutoff Mechanism: Delta V Detection and Timer Control
Delta V Detection   5mV per cell for "AA-AAA-C-D"
Max Timer Control   2 or 4 "AA" / 1 or 2 "AA-C-D" 3 hours
6 or 8 "AA" / 3 or 4 "AA-C-D" 6 hours
2 or 4 or 6 or 8 "AAA" 3 hours

Charger Input : DC 12V, 1A
AC Adapter Input: 100-240V AC 50/60Hz 0.35A
AC Adapter Output: DC 12V, 1A
Weight (charger): 335 grams (11.8 oz.)
Dimensions (mm): 200 x 100 x 54 (H x L x W)
Volume (cm³): 12525 (charger), 1248 (AC adapter)
Safety Features: Delta V Charging Cut Off
Short Circuit and Reverse Polarity Protection
Safety Timer to Prevent Over Charge
Bad Battery Detection

Important Notice
This datasheet contains information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc.
Contents herein do not constitute a warranty.

Energizer.