

SOUTH CHINA NATIONAL CENTER OF METROLOGY
GUANGDONG INSTITUTE OF METROLOGY



# 安全技术说明书

报告编号 Report No.

DCW201604403

第1页,共9页

Page of

委托方 Client

深圳市杰特明电子科技有限公司

委托方地址 Add. of Client

深圳市宝安区龙华街道大浪南路墩背工业区永昌盛厂房1栋3楼

样品名称 Description

锂电池

型号规格 Model /Type ICR10180

制造厂

深圳市百冠电池有限公司

Manufacturer 制造厂地址 秋初110日/医·日阳公司

Add. Of Manufacturer 中国广东深圳西乡固戍下围园新村世通亿利工业园4F

接收日期 Date of Receipt 2016 年 09 月 07 日 Y M D

检查日期 Censor date 2016 年 09 月 12 日 ソ M D

批准人 Approved Signatory

核验 Checked by 检验 Inspected by





本中心地址:中国广州市广园中路松柏东街30号

邮政编码 (Post code):510405

电话: (8620)86594172 传真: (8620)86590743 投诉电话: (8620)26296063 E-mail: scm@scm.com.cn

Add: No.30, Songbaidong Street, Guangyuangzhong Road, GuangZhou, P.R. China
Post Code: 510405 Tel: (8620)86594172 Fax: (8620)86590743 Complaint Tel: (8620)26296063

证书真伪查询: www.scm.com.cn; www.mtpsp.com Certificate Authenticity Identify: www.scm.com.cn; www.mtpsp.com



SOUTH CHINA NATIONAL CENTER OF METROLOGY
GUANGDONG INSTITUTE OF METROLOGY



报告编号: DCW201604403

Report No.

第2页,共9页 Page of

### 说明

### DIRECTIONS

1.本中心是国家质量监督检验检疫总局在华南地区设立的国家法定计量检定机构,本中心的质量管理体系符合ISO/IEC 17020标准的要求,并经中国合格评定国家认可委员会(CNAS)认可,认可证书号为: CNAS IB0354.

This laboratory is the National Legal Metrological Verification Institution in southern China set up by the General Administration of Quality Supervision, This laboratory's quality management system is in accordance with ISO/IEC 17020 Standard and accredited by China National Accreditation Service for Conformity Assessment under Laboratory Accreditation Certification No. CNAS IB0354.

2.本中心所出具的数据均可溯源至国家计量基准和国际单位制(SI)。

All data issued by this laboratory are traceable to national primary standards and International System of Units (SI).

### 3.技术依据:

Reference documents:

联合国《关于危险货物运输的建议书规章范本》(第18版)

UN Recommendations on the Transport of Dangerous Goods Model Regulation (Eighteenth revised edition) 联合国《关于危险货物运输的建议书—试验和标准手册》(第5版以及修订版1和修订版2)

UN Recommendations on the Transport of Dangerous Goods manual of tests and criteria

(Fifth revised edition Amendment 1 and Amendment 2)

国际航空运输协会《危险货物规则》(第57版)

IATA Dangerous Goods Regulation (57th)

国际海事组织《国际海运危险货物规则》(第37-14版)

IMO International Maritime Dangerous Goods Code (37-14 edition)

ISO 11014:2009 化学品安全技术说明书一内容和项目顺序

ISO 11014:2009 Safety data sheet for chemical products-Content and order of sections

GB/T 16483-2008 化学品安全技术说明书 内容和项目顺序

GB/T 16483-2008 Safety data sheet for chemical products-Content and order of sections

4.地点:

Place:

地点 本中心货物鉴定室

Place (authentication Lab for goods)





SOUTH CHINA NATIONAL CENTER OF METROLOGY
GUANGDONG INSTITUTE OF METROLOGY

报告编号: DCW201604403 Report No. 原始记录号: 020164403

Record No.

第 3 页,共 9 页 Page of

一. 样品信息 Sample information


THE PERSON			
样品名称 Sample Name	锂电池	样品型号 Tye	ICR10180
标称电压 Nominal voltage	3.7V	额定容量 Rated capacity	70mAh 0.259Wh
样品外观 Shape		柱形 Cylindrical	SON SON SON

### 二. 内容与说明 Content and instructions

### 1. 化学品及企业标识 Chemical product and company identification

化学品名称 Name of chem	ical product	锂电池
制造商 Manufacturer	名称 Name	深圳市百冠电池有限公司
	地址 Address	中国广东深圳西乡固戍下围园新村世通亿利工业园4F
	电话 Telephone number	+860755-33118013
	应急电话 Emergency telephone number	+860755-33118013
	传真 Fax number	+860755-33118012
	电子邮件	







报告编号: DCW201604403

Report No.

原始记录号: 020164403

Record No.

第 4 页,共 9 页 Page of

### 2. 危险性概述 Hazards identification

### 1) 主要的物理及化学危险性 Important Physical and chemical hazards

在强压变形、拆解、短路时有起火爆炸与化学烧伤等危险,在高温环境或放置于火焰环境中、超负荷使用时有起火爆炸危险.

When the battery is in extreme pressure deformation, high-temperature environment, overload, short-circuit condition, or disassemble the battery, an explosion of fire and chemical burn hazards may occur.

### 2) 对人体健康影响 Effects of the human health.

### 眼睛 Eyes

正常使用下无危害性,但在拆解、弯曲、短路可能会引起电池起火爆炸伤害眼睛。破损时挥发出气体会对眼睛产生刺激。

In normal condition, Contact between the battery and eyes will not cause any harms. However, the gas Volatilize from a damaged battery may be harmful to eyes.

#### 皮肤 Skin

正常情况下接触无对皮肤危害性。在电池破损情况下接触有可能引起化学烧伤或皮肤过敏发炎症状。

In normal condition, Contact between the battery and skin will not cause any harms. Contact with a damaged battery may cause skin allergies or chemical burns.

#### 吸入 Inhalation

完好电池并无挥发出可供吸入气体情况。破损时会挥发出微量气体会刺激呼吸道,严重者可能引起过敏反应。

A battery volatilizes no gas unless it was damaged. Damaged battery will volatilize little gas that may stimulate the respiratory tract or cause an anaphylaxis in serious condition.

### 食入 Ingestion

食入会对呼吸道产生伤害、对肠胃产生烧伤,严重会造成永久性损害

Swallowing battery will be Damaged to the respiratory tract and Cause chemical burns to the stomach; in serious conditions it will cause Permanent damage.







报告编号: DCW201604403 Report No. 原始记录号: 020164403 Record No. 第 5 页, 共 9 页 Page of

### 3. 成分/组成信息 Composition/information on ingredients

化学名(化学式) Chemical Name(chemical formula)	成分含量Concentration or concentration ranges (%)	CAS号 CAS No.	
Lithium Cobalt Oxide (CoLiO2)	15-40	12190-79-3	
Graphite	10-30	7782-42-5	
Phosphate(1-), hexafluoro-, lithium	10-30	21324-40-3	
Copper	7-13	7440-50-8	
Aluminum foil	5-10	7429-90-5	
Nickel	1-5	7440-02-0	

### 4. 急救措施 First-aid measures

### 眼睛 Eyes

如有接触损坏电池,立即用清水清洗眼睛15分钟以上直至刺痛/刺激感消失为止,并及时去就医。

If your eyes come into contact with a damaged battery, flush with copious amount of water for at least 15 minutes until the stinging and irritation subside, and Seek immediate medical attention.

### 皮肤 Skin

如有接触,立即脱下被污染衣服并用大量清水冲洗皮肤或淋浴,如灼伤感持续立刻去就医。 If your skin comes into contact with a damaged battery, immediately take off contaminated clothing and flush your skin with copious amount of water or have a shower. Seek immediate medical attention if burning sensation continues.



SOUTH CHINA NATIONAL CENTER OF METROLOGY
GUANGDONG INSTITUTE OF METROLOGY



报告编号: DCW201604403 Report No. 原始记录号: 020164403 Record No.

第 6 页, 共 9 页 Page of

### 吸入 Inhalation

立刻转移到空气新鲜环境下呼吸新鲜空气,休息。如出现呼吸困难或头晕头痛等症状立刻请人陪同去就医。

Remove to fresh air immediately and have a rest, If you feel dyspnea, dizziness or headache, seek immediate medical attention.

### 食入 Ingestion

如果食入电池,不要催吐且不要再吃下食物或喝饮料,立刻就医

If battery or open battery is ingested, do not induce vomiting or give food or drink. Seek medical attention immediately.

### 5. 消防措施 Fire-fighting measures

此产品在强压弯曲或短路等情况下容易起火并冒出大量烟雾,应正确使用并置于阴凉环境下,避免放置在高温、日光照射及受重压的地方。如发生起火,戴上防毒面具在条件允许情况下洒水或用灭火器让毗邻的未起火电池降温避免火势蔓延并用工具把起火电池和其他电池分离,让其自然熄灭;或用大量的水灭火,但起火电池一般都会在内部化学物质反应完后火才熄灭下来。如果有电池起火火势较大,立刻报火警并疏散人员到安全地方。

This battery can get fire easily and made a lot of smoke under the forced bending and short-circuit condition, so it should be properly used and placed in a cool environment and Avoid placing the battery package under heat, pressure and direct sunlight. In the event of fire, wear gas masks and cool the adjacent batteries and control the spread of fire with water or extinguishers, separate the fire batteries with other batteries as conditions permit, let the fire naturally extinguished, otherwise put out the fire with lots of water. In normal condition the fire is not extinguished until the reactions that between the chemicals contained in the battery are completed. In the event of a big fire, report the fire immediately and evacuate to a safe place.

### 6. 泄漏应急处理 Accidental release measures

将溢漏物与电池清扫,并放进干燥可密闭的金属容器或材质不易燃的容器中,交由电池回收企业进行环保处理。避免电池弃扔到自然环境中。

Clean the spills and batteries, place them in a dry sealed metal container or nonflammable material container, and bring them to battery recycling companies to deal with environmental protection. Do not throw away the damaged batteries or waste batteries.



### SOUTH CHINA NATIONAL CENTER OF METROLOGY GUANGDONG INSTITUTE OF METROLOGY



报告编号: DCW201604403 Report No. 原始记录号: 020164403 Record No. 第 7 页, 共 9 页 Page of

### 7. 操作处置与储存 Handling and storage

### 操作 Handling

不能擅自组装拆解电池或短路,不能让电池接近火源。运输电池应避免暴力装卸电池货物、避免电池受到挤压或剧烈振动。

Do not assemble and disassemble a battery, battery short-circuit is not allowed too. Keep the battery away from the fire. When transporting these batteries, the battery should be careful handling to avoid the battery being squeezed or excessive vibration.

### 储存 Storage

长时间存储前先充满电。电池应储存于阴凉环境中。

The battery should be fully charged before long term storage. The battery should be stored in a cool environment.

### 8. 接触控制和个体防护 Exposure controls/Personal Protection

### 工程控制 Engineering control

选择合理的通风设备,足够量的防毒面具灭火器及水源,配备存放泄漏电池的金属容器。配备洗浴设备。

Choose the suitable ventilation equipment; provide sufficient quantity of fire extinguishers, gas mask and water; equip with metal storage containers and bathing equipments.

### 呼吸系统防护 Respiratory protection

正常情况下无必要作防护 Normally there is no need to do protection.

### 眼睛防护 Eye protection

正常情况下无必要作防护 Normally there is no need to do protection.

### 身体和皮肤防护 The body and skin protection

正常情况下无必要作防护 Normally there is no need to do protection.

### 9. 理化特性 Physical and chemical properties

### 物品外观与型状Object appearance and shape

圆柱形固体 Cylindrical solid.

### 气味 Odour

无 None



### SOUTH CHINA NATIONAL CENTER OF METROLOGY GUANGDONG INSTITUTE OF METROLOGY



报告编号: DCW201604403 Report No. 原始记录号: 020164403 Record No. 第 8 页, 共 9 页 Page of

### 10. 稳定性和反应性 Stability and reactivity

### 稳定性 Stability

正常环境下稳定。 Stable under the regular environment.

### 应避免的条件 Should avoid conditions

高温或过湿环境,撞击震动或受挤压,正负极反接使用。

High temperature, wet environment, mechanical shock, vibration, crush, reverse polarity used should be avoided.

### 不相容物质 Incompatible materials

无 None

### 危险的分解产物 Hazardous decomposition products

在起火时会释放出刺鼻的浓烟雾。

When the battery catches fire, it will release pungent thick smoke.

### 11. 毒理学信息 Toxicological information

正常情况下接触电池无毒性作用。

In normal condition, contact with the battery is non-toxic.

### 12. 生态学信息 Ecological information

正常处理电池不会对生态环境产生影响。

Proper disposal of battery does not present ecological hazard.

### 13. 废弃处置 Disposal considerations

交由电池回收企业进行回收处置,不能随意丢弃于环境中。具体参照有关国家相关法规。 It needs to be referred to the waste battery recycling companies for recycling disposal, cannot arbitrarily discarded in the environment. Specific conditions reference to the relevant national laws and regulations.







报告编号: DCW201604403

Report No.

原始记录号: 020164403

Record No.

第 9 页,共 9 页 Page of

### 14. 运输信息 Transport information

该电池样品为锂离子/聚合物电池,该电池型号已通过UN38.3测试。

This battery sample is lithium ion/polymer battery This battery type is proved to meet the Requirements tests in the UN *Manual of Tests and Criteria*, Part III, subsection 38.3.

可按IATA《危险品规则》中包装说明PI965~PI967相关规定进行包装空运。

Can be transport by air according to the Packing Instructions 965, 966 and 967 of IATA Dangerous Goods Regulations relevant regulations.

可按IMO《国际海运危险货物规则》特殊规定第188条相关规定进行包装海运。

Can be transport by sea according to the special provision 188 of IMO International Maritime Dangerous Goods Code relevant regulations.

15 11/4	4 / 三 自			All Same
15. 其作	四百万	ner in	forma	$\mathbf{m}$

无 None.

