



## 1050 Micro

From small sensitive components to smartphones, protect your gear from the elements in a crushproof, watertight, & dustproof Micro Case from Pelican.

- **\*Case is able to be submerged under 1 meter of water for up to 30 minutes in accordance with IP67 testing parameters**
- **Available in clear with color liner or solid**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Carabiner
- Easy open latch
- Lifetime Guarantee of Excellence
- Rubber liner for extra protection doubles as o-ring seal
- Stainless steel hardware



### DIMENSIONS

|                         |  |
|-------------------------|--|
| <b>Interior (LxWxD)</b> | 6.31 x 3.68" x 2.75 (16 x 9.3 x 7 cm)        |
| <b>Exterior (LxWxD)</b> | 7.99 x 5.06" x 3.12 (20.3 x 12.9 x 7.9 cm)   |
| <b>Lid Depth</b>        | 0.69" (1.8 cm)                               |
| <b>Bottom Depth</b>     | 1.94" (4.9 cm)                               |
| <b>Total Depth</b>      | 2.63" (6.7 cm)                               |
| <b>Int Volume</b>       | 0.04 ft <sup>3</sup> (0.001 m <sup>3</sup> ) |

### MATERIALS

|                   |                                      |
|-------------------|--------------------------------------|
| <b>Body</b>       | Polycarbonate (PC)                   |
| <b>Latch</b>      | Xylex                                |
| <b>O-Ring</b>     | Thermoplastic Rubber                 |
| <b>Pins</b>       | Stainless Steel                      |
| <b>Foam</b>       | TL - 426 4 lb. Esther                |
| <b>Purge Body</b> | Polycarbonate (PC)                   |
| <b>Purge Vent</b> | Polyester Spun-Bond ePTFE Oleophobic |

### COLORS

|   |  |  |   |
|---|--|--|---|
|  Black   |  OD Green       |  Yellow       |  Tan          |
|  Seafoam |  Yellow - Clear |  Blue - Clear |  Bright Green |

### WEIGHT

|                           |                   |
|---------------------------|-------------------|
| <b>Weight With Foam</b>   | 0.83 lbs (0.4 kg) |
| <b>Weight Empty</b>       | 0.81 lbs (0.4 kg) |
| <b>Buoyancy</b>           | 1.74 lbs (0.8 kg) |
| <b>Master Pack Weight</b> | 5.88 lbs (2.7 kg) |

### TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -10°F (-23.3 °C) |
| <b>Maximum Temperature</b> | 199°F (92.8 °C)  |

## CERTIFICATIONS

---

**IP67**

## OTHER

---

|                     |     |
|---------------------|-----|
| <b>Minimum Pack</b> | 6   |
| <b>Master Pack</b>  | 6   |
| <b>Military</b>     | yes |

## ACCESSORIES

---



**1051**  
Replacement Case Liner



**1052**  
Pick N Pluck™ Foam Insert



**1500CI**  
Corrosion Intercept Kit

---

### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 02-09-24*