

<u>TLR-10[®] G</u>

RAIL-MOUNTED TACTICAL LIGHT WITH GREEN LASER

DESCRIPTION:	Lightweight & compact, the TLR-10[®] G is a full frame weapon-mounted tactical light with an integrated green laser. This light features the latest in LED technology for high-lumen operation and provides 1.5 hours of continuous run time from two CR123A lithium batteries. 1000 lumens of output deliver a powerful beam with extensive range and good peripheral coverage.
CASE MATERIAL:	Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish Switch housing: Impact- and chemical-resistant engineered polymer
DIMENSIONS:	Width: 1.18 in (2.98 cm) Height: 1.50 in (3.81 cm) Length: 3.87 in. (9.82 cm)
WEIGHT:	4.62 oz (131 grams) with two (2) batteries (included with purchase)
LENS:	High temperature, shock-mounted, impact-resistant BOROFLOAT® glass 510-530nm green laser
LIGHT SOURCE:	LED: White, impervious to shock with a 50,000-hour lifetime
LIGHT OUTPUT:	1000 lumens, 10,000 candela peak beam intensity and 200 m beam distance Custom TIR optic produces a concentrated beam with optimum peripheral illumination. Optimized electronics provide regulated intensity. Laser provides long-range targeting.
ON/OFF:	Rear switches left and right of the trigger guard provide ambidextrous operation. Available with high and low actuators Quick press for constant on operation and press and hold for momentary operation. 3 Modes: Laser only, LED only, both laser and LED; selectable by pressing both switches Double tap either switch within ¼ second to activate strobe (if enabled).
RUN TIME:	LED: 1.5 hours to 10% output level LED and laser combined: 1.5 hours to the 10% output level Laser only: 11 hours regulated output Strobe: 3 hours
BATTERY:	Two (2) 3-volt CR123A lithium batteries with a storage life of 10 years
FEATURES:	Lightweight and slim High-power LED for extreme brightness Ambidextrous operation One handed snap-on and tighten interface keeps hands away from muzzle when attaching or detaching Securely fits a broad range of weapons using key kit provided Extensively live-fire tested Operating temperature: -40°F to +120°F IPX4-rated design; water-resistant operation Serialized for positive identification
APPROVALS:	CE 🖁 Meets applicable European Community Directives
WARRANTY:	Streamlight's Limited Lifetime Warranty
OPTIONAL ACCESSORIES:	Mounting adapters

BOROFLOAT® is a registered trademark of SCHOTT AG.

EXPORT CONTROLS: The export of this product is subject to the jurisdiction of the U.S. Department of Commerce Export Administrative Regulations ("EAR"). The exported sale, transfer or shipment of this product is expressly prohibited by U.S. Law and is subject to export restrictions, including export licenses and accompanying documentation and authorization, the absence of which may result in fines and penalties. Furthermore, diversion, resale, re-export or transfer of this product is contrary to U.S. Law and is prohibited without the prior written consent of the U.S. Department of Commerce. Compliance with any and all export controls are the sole responsibility of the distributor.