

PRODUCT FACT SHEET

PROTAC® 2.0

DESCRIPTION: The ProTac® 2.0 is a 2,000-lumen tactical flashlight that uses a proprietary Streamlight SL-B50® protected Li-Ion rechargeable battery. The ProTac® 2.0 features a tactical tail cap switch for momentary or constant on operation and three different user-selectable programs. The Streamlight SL-B50® charges directly via USB-C port in the body of the battery. The battery is keyed to ensure proper alignment of the charging port. Packaged with a USB-C cord, removable pocket clip, and holster. CASE MATERIAL: 6000 series machined aircraft aluminum with Type II MIL-Spec anodized finish. Available in black. **DIMENSIONS:** Length: 6.10 in (155mm) Head Diameter: 1.46 in (37 mm) Body Diameter: 1.02 in (26 mm) WEIGHT: 8.25 oz (234 g) with (1) Streamlight SL-B50® protected Li-Ion USB-rechargeable battery (included in purchase) LENS: Glass with anti-reflective coating; gasket-sealed LIGHT SOURCE: LED technology, impervious to shock with a 50,000-hour lifetime LIGHT OUTPUT: See chart. Fully regulated output for consistent lumen performance over the entire battery life. ON/OFF: Multi-function, push-button tactical tail switch with momentary and latching constant on operations. One-handed operation of momentary, variable intensity, or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only, or low/medium/high. RUN TIME: See chart below. All run time claims are to 10% of initial lumen output. **BATTERY:** One (1) Streamlight SL-B50® protected 4,900mAh Li-Ion USB-rechargeable battery with on-board safety control. Recharges in 6 hours. FEATURES: LED technology for extreme brightness IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes. All openings O-ring sealed. 2-meter impact resistance tested Anti-roll face cap Serialized for positive identification CE K Meets applicable United Kingdom and European Community Directives **APPROVALS:** (BC) CEC Compliant WARRANTY: Streamlight's Limited Lifetime Warranty **OPTIONAL ACCESSORIES:** Holster, USB-C charge cord, SL-B50® battery OUTPUT:

FL 1 Standard	HIGH	MEDIUM	LOW
July -	2000	570	100
4 1	LUMENS	LUMENS	LUMENS
S	2h 30min	4h 30min	25h
	262m	142m	60m
	17,300cd	5000cd	890cd

Strobe Run Time: 4h 25min