

KNUCKLEHEAD® HAZ-LO® (SPOT)

MULTI-PURPOSE WORKLIGHT WITH ARTICULATING HEAD





Material/Lens Housing, base and battery housing made from high impact super tough nylon offering exceptional durability. All openings are O-ring sealed for weather resistance. Circular rare-earth magnet surrounded by durable nickel plated steel housing. One-way valve for case venting. Available in orange. Unbreakable polycarbonate lens with silicone anti-scratch coating assembled in a heavy duty bezel. O-ring sealed.

Dims/Weight

Height: 9.20 in. (23.4 cm); Width: 2.85 in. (7.2 cm); Thickness (at magnet): 2.75 in. (7.0 cm)

Weight: NiCd: 23.1 oz (655 grams)* Alkaline: 18.3 oz (519 grams)

Light Source

One white LED, impervious to shock with a 50,000 hour lifetime. Single parabolic reflector provides a tighter beam for longer range target illumination

Output/

Run time

- High for a tight, far-reaching beam: 150 lumens; 12,900 candela; 227m beam distance; runs 3.5 hours

- Low for when less light is ideal and for longer run times; 55 lumens; 4,300 candela: 131m beam; runs 12 hours
- Moonlight for low-level lighting and extended run times runs 20 days
- Flash for signaling runs 8 hours

Rubber dome push-button actuator provides easy operation even when wearing heavy gloves Switch

NIMH battery pack rechargeable up to 1,000 times; also accepts 4 "AA" alkaline batteries Battery

Features

- Full 360 degree rotation head with 210 degrees of articulation
- IPX4 water-resistant; 2m impact resistance tested
- · Removable magnet with 135 lb pull strength
- · Super strong pocket clip

Approvals Class I & II Division 1, Groups C,D,F,G; Class III; T-Code: T4; Exia;

NON-INCENDIVE: Class I Division 2; Groups A,B,C,D, T-CODE T4

MSHA Permissible Flashlight; Approval. No. 20-4140001-0: Tested for Intrinsic Safety in Methane-Air mixtures only. Charge or replace batteries in fresh air only. Charger meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position

Meets applicable European Community Directives.

Warranty

Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FÍTNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW.

You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Part #
Knucklehead HAZ-LO Spot - 120V AC/12V DC - Yellow	080926-91727-9	91727
Knucklehead HAZ-LO Spot - 120V AC/12V DC - Orange	080926-91757-6	91757
Knucklehead HAZ-LO Spot - 120V AC - Yellow	080926-91722-4	91722
Knucklehead HAZ-LO Spot - 120V AC - Orange	080926-91752-1	91752
Knucklehead HAZ-LO Spot without charger - Yellow (NiCd) (not for sale in EU)	080926-91721-7	91721
Knucklehead HAZ-LO Spot without charger - Orange (NiCd) (not for sale in EU)	080926-91751-4	91751
Knucklehead HAZ-LO Spot - Alkaline - Yellow	080926-91742-2	91742
Knucklehead HAZ-LO Spot - Alkaline - Orange	080926-91744-6	91744

	Item	UPC	Part #
	DC2 direct wire charge cord	080926-22050-8	22050
	DC1 Charge Cord	080926-22051-5	22051
	100V/120V AC charge cord	080926-22060-7	22060
	230V AC charge cord	080926-22061-4	22061
	240V AC charge cord	080926-22062-1	22062
	Steady Charge (SC) Plug-In Charger Holder	080926-90010-3	90010
	NiMH Battery Pack	080926-90336-4	90336
	Bank Charger (SC) 120V AC	080926-90400-2	90400
	Bank Charger (SC) 230V AC	080926-90600-6	90600
	Bank Charger 12V DC	080926-90401-9	90401
	Alkaline battery carrier (Batteries not included)	080926-90542-9	90542