

PRODUCT FACT SHEET

TLR-6 HL® // TLR-6 HL® G TACTICAL LIGHT WITH RED OR GREEN LASER

DESCRIPTION: The rechargeable **TLR-6 HL**® weapon-mounted light with a high-power LED and integrated red or

green aiming laser features tool-less rechargeable battery replacement without removal from the weapon or the need to re-sight the laser. The light provides 300 lumens for 20 minutes of run time per battery when in light/laser mode, giving the user 1 hour of power when using all three included batteries. Designed to securely attach to the rail and trigger guard of select subcompact handguns.

CASE MATERIAL: Impact-resistant engineered polymer

DIMENSIONS: Length: 2.50 in (6.35 cm) Width: 0.85 in (2.16 cm) Height: 1.56 in (3.96 cm)

WEIGHT: 1.12 oz (31.8 g) with battery (included)

LENS: Tempered glass with shock-resistant gasket seal.

LIGHT SOURCE: White LED, impervious to shock with a 50,000-hour lifetime.

640-660 nm Red laser 510-530 nm Green laser

LIGHT OUTPUT: 300 lumens, 4,250 candela peak beam intensity, and a 130 meter beam distance.

Parabolic reflector produces a balance of beam and peripheral illumination.

Optimized electronics provide regulated intensity.

Laser provides long-range targeting.

ON/OFF: Left and right handed switches for ambidextrous operation.

Quick press of either switch for constant on operation or press and hold for momentary operation.

Three (3) user-selectable modes: light only; laser only; or light/laser combined.

RUN TIME: LED only or LED/laser: 20 minute runtime.

Red laser only: 9 hour runtime. Green laser only: 5 hour runtime.

BATTERY: Powered by one (1) proprietary Streamlight SL-B2[™] rechargeable battery.

The package includes one (1) battery in the light and two (2) in the included USB-C charge case. Batteries replaceable with unit mounted on weapon. No need to re-sight laser after each battery

change.

FEATURES: Designed for use with GLOCK® G42/G43, GLOCK® rail mount models (see compatibility list), Smith &

Wesson® M&P® Shield™, and SIG SAUER® P365® handguns.

Ultra lightweight and compact. Ambidextrous operation.

Windage and elevation adjustment screws mounted in bushings for long life and dependable zero

retention of laser.

Operating temperature: -20°F to +120°F. 1-meter impact resistance tested. Serialized for positive identification.

APPROVALS: CE CA Meets applicable United Kingdom and European Community Directives

WARRANTY: Streamlight's Limited Lifetime Warranty

ACCESSORIES: Replacement SL-B2 batteries, Charger with batteries

All rights reserved. GLOCK® is a registered trademark of Glock, Inc. Smith & Wesson® and M&P® Shield™ are trademarks or registered trademarks of Smith & Wesson Inc. SIG SAUER® and P365® are registered trademarks of SIG Sauer, Inc. Streamlight has not sought endorsement from any of the Companies mentioned in this paragraph.

EXPORT CONTROLS: The export of this product is subject to the jurisdiction of the U.S. Department of Commerce Export Administrative Regulations ("EAR"). The exported sale, transfer, or shipment of this product is expressly prohibited by U.S. Law and is subject to export restrictions, including export licenses and accompanying documentation and authorization, the absence of which may result in fines and penalties. Furthermore, diversion, resale, re-export, or transfer of this product is contrary to U.S. Law and is prohibited without the prior written consent of the U.S. Department of Commerce. Compliance with any and all export controls are the sole responsibility of the distributor.

Issued: 06/28/2023

Revised: 09/28/2023 Rev: 2 Made in China, Document #395