

Tenergy 11.1V 2200mAh Lithium Ion Battery Pack

Product Name:	Tenergy Lithium Ion Battery Pack with PCB	
Product Number:	31012	
Battery Size:	11.1V 2200mAh	

1. Scope

The specification describes the technology parameters and testing standard for the lithium ion rechargeable pack supplied by Tenergy Corporation.

2. References

This specification is referenced GB/T18287-2000、UL1642、IEC61960-1:2000.

3. Basic characteristics

3.1 Capacity	Nominal Capacity : 2200mAh (0.5C _A Discharge)
	Minimum Capacity: 2150mAh (0.2C _A Discharge)
3.2 Nominal Voltage	11.1 V
3.3 Internal impedance	≤ 240mΩ(with PTC)
3.4 Discharge Cut-off Voltage	8.4V
3.5 Max Charge Voltage	12.9V
3.6 Standard Charge Current	0.5C _A
3.7 Rapid Charge Current	1C _A
3.8 Standard Discharge Current	0.5C _A
3.9 Rapid Discharge Current	1C _A
3.10 Max Discharge Current	2.0 C _A
3.11 Weight	140±4g
3.12 Max. Dimension	Length(L): 68mm Width: 56mm



	Height (H): 19mm
3.13 Operating Temperature	Charge 0 ~ 45°C
	Discharge -20 ~ 60°C
3.14 Storage Temperature	Within 1 month -5 ~ 35°C
	Within 6 months 0 ~ 35°C

4. Standard Conditions for Test

Unless specified, all tests should be conducted within one month after the delivery under the following conditions: Ambient Temperature: 25±5°C; Relative Humidity: 65±20%

4.1 Standard Charge:	Constant Current and Constant Voltage (CC/CV) Current = 1100mA End-up Voltage = 12.9 V End Current = 24mA
4.2 Standard Discharge:	Constant Current (CC) Current = 1100mA End Voltage = 8.4V

5. Characteristics

※In this section, the Standard Conditions of Tests see the part 4.

5.1 Electrical Performances

Item	Test procedure	Requirements
5.1.1 Nominal Voltage	The average value of the working voltage in the whole discharge progress.	11.1V
5.1.2 Discharge Performance	The discharge capacity of the cell, which is measured at 1C ₅ A (or 0.5CA) current discharge to 8.4V within 1 hour after completely charge.	≥57(or 120)min
5.1.3 Capacity Retention	After 28 days storage at 25±5°C after completed charge, the residual capacity is above 90%.	Capacity≥80%
5.1.4 Cycle Life	After 300 cycles in 100% DOD charge and	≥300 cycles



	discharge at 0.5CA current, the residual discharge capacity is above 60% of nominal capacity.	
5.1.5 Storage	(Within 3 months after manufactured) after standard charged 40-50% capacity and stored at ambient temperature 25±5°C、65±20%RH for 12 months, the storage expiry and the cell completely charged, the cell is discharged at 0.2 CA current discharge to 8.4V.	Discharge time≥4h

5.2 safety Performances

5.2.1 Short Circuit	The cell is to be short-circuited by connecting the positive and negative terminals of the cell directly with copper wire with a resistance less than 0.05Ω.	No fire, no explosion.
5.2.2 Impact Test	Impacting of a cell on a hard surface following a hammer of 10 kilograms free fall from 1m height.	No fire, no explosion.
5.2.3 Overcharge (3C/15V)	The cell that connect with the thermocouple is put in the fume hood, the positive and negative terminals are connected by a permanent constant electrical source, regulate current to 3 CA and voltage to 15 V. Then charge the cell until voltage is 15 V, current about 0A. Monitor the temperature change of cell when the temperature of cell is about lower 10°C than peak value, the test is over.	No fire, no explosion.
5.2.4 Thermal shock	After standard charging, heat cell to 150±2°C at rate of 5±2°C/min and keep 10 minutes.	No fire, no explosion.



5.3 Environmental tests

5.3.1 High temperature performance	The fully charged cell is put in the surroundings of $55\pm 2^{\circ}\text{C}$ for 2 hours, and then it is discharged to the 8.4V at 1CA current rate.	Capacity $\geq 80\%$
5.3.2 Low temperature performance	The charged cell is put 16-24 hours at $-20\pm 2^{\circ}\text{C}$ and then discharge to 8.4V at 0.2 CA current rate.	Capacity $\geq 50\%$
5.3.3 Vibration Test	After standard charging, the cell is fixed on the platform and be subjected to vibrate on following frequency 10~55Hz and amplitude vibration for 30 minutes with direction of X, Y. Vibration Frequency: 10~30Hz, vibration amplitude 0.38mm. Vibration Frequency: 30~55Hz, vibration amplitude 0.19mm	
5.3.4 Drop Test	The cell is to be dropped from a height of 1m to hard board in X、Y、Z directions for twice respectively. Then discharge the cell at 1CA current rate to 5.6V, and undertake more than three circles of standard charge and discharge at 1CA current rate.	No fire, no explosion.

6. Packing

Keep the cells at the half-fully charged state before packing.

7. Transportation:

Violent shaking, bumping, rain and flaring sun shall be forbidden during the transportation. Keep the cells at the half-fully charged state.

8. Storage

Please keep the cell in the cool and dry environment: Within 1 month $-5 \sim 35^{\circ}\text{C}$ or Within 6 months, $0 \sim 35^{\circ}\text{C}$, Relative humidity $\leq 75\%$, Keep the cells at the half-fully charged state.

9. Warranty period of this product is 6 months from leaving plant.



10. We will not guarantee against any accidents occurring due to usage against this specification.

11. The information in this specification subject to change without prior notice.

12. The information contained in this document is for reference only and should not be used as a basis for product guarantee or warranty. For applications other than those described here, please consult Tenergy directly.

13. Caution:

13.1 Please read the specification carefully before testing or using the cell, as improper handling of Lithium-ion cell may result in loss of efficiency, heating ignition, electrolyte leakage or even explosion.

13.2 While testing the cell of charging and discharging, please use the testing equipment special for Li-ion cell. Do NOT use the ordinary source of constant current and constant voltage, which fails to restrict charge and discharge to cell in order to prevent the cell from being overcharged and over-discharged, triggering cell malfunction or explosion.

13.3 When charging and discharging to the cell or packing it into the equipment, do NOT reverse the terminals of cathode and anode or it will make the cell overcharging and over-discharging, causing the cell to lose efficiency seriously and even explode.

13.4 Do NOT weld the cell directly, do not disassembly the cell.

13.5 Do NOT put the cell together with such metal products as necklace, hairpin, coin or screw in the pocket or in the bag; neither store them together. Do NOT connect the positive and negative electrode directly with such conductive materials as metal, or it may make the cell short-circuit.

13.6 Do NOT beat, throw or trample the cell. Do NOT put the cell into the washing machine or the high-pressure container.

13.7 Do NOT put the cell close to heat source, for instance, fire, heater etc. Do NOT use the cell under the circumstance of burning sun or the temperature exceeding 60°C, or it may cause the cell to generate heat, heating ignition and loss of efficiency.


13.8 Do NOT get the cell wet or throw the cell into water. When not use, it should be placed in the dry and low temperature environment.

13.9 While using, testing or preserving the cell, if you find the battery become hot , distribute smell , change color, deform or any other abnormality, please stop using or testing immediately, and attempt to isolate and keep away from the cell.

13.10 If the cell leaks, the electrolyte gets into the eyes, do not rub eyes, instead, rinse the eyes with plenty of water, and seek medical service. If the electrolyte gets onto the skin or clothe, wash it with plenty of water immediately.

14. PCB Specification

Tenergy adds the PCB for all the lion battery pack





Tenergy Corporation

436 Kato Terrace
Fremont, CA 94539 USA

Tel: 1(510)687-0388 ext 308 Fax: 1(510)687-0328

www.TenergyBattery.com email: sales@tenergybattery.com

Programer		DATA	Annotation
	Over charge protect Volt	4. 35V ± 25mV	add number for cell
	Over charge recovery volt	4. 15V ± 50mV	add number for cell
	Over discharge protect volt	2. 40V ± 80mV	add number for cell
	Over discharge recovery volt	3. 0V ± 100mV	add number for cell
	Carrent protect	6. 5A (Max)	12. 6V
	Working carrent	3. 0A (Max)	10. 8V
	Overcharge protect time	1. 0S (Typical)	
	Overdischarge protect time	100mS (Typical)	
	Carrent protect time	10mS (Typical)	
	Working consumption	30uA (Max)	
	Sleep carrent	0. 1uA (Max)	
	Working resistance	≤ 130m Ω	
	0V charge	有 Yes	
	Work temperature	-40~+85°C	
	Charge condition	12. 6V / 2A (Max)	CC/CV
Size	Length	50mm ± 0. 3mm	
	width	16mm ± 0. 2mm	
	thickness	3. 5mm (Max)	